
TECHNICAL SPECIFICATION

CONE CRUSHER CS SERIES
CS420





DIMENSIONS (mm)

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
2 902	1 020	540	692	692	1 285	620	1 703	3 365	843	1270	1 090	1 400	850	1 156	861	770	650

WEIGHTS (kg)

Feed hopper	Spider cap	Topshell, complete	Mainshaft assembly complete	Eccentric, complete	Bottomshell assembly complete	Pinionshaft housing complete	Hydroset cylinder complete	Total Weight (approx.)	Oil tank
200	65	2 300	1 600	255	2 360	145	–	6 800	270

PERFORMANCE

Nominal capacities MTPH	Chamber	EC	C
	CSS	120 – 135	100 – 115
	GG	125	105
	SH	190	165
	ML	240	200
Max motor power (kW)		90	90
Ecc. Throw (mm)		16 – 25	16 – 25
	16		77
	19	–	82–110
	22	102–118	87 – 116
	25	108 – 144	92 – 123
	29	115 – 154	98 – 113
	32	121 – 162	103
CSS (mm)	35	127 – 145	–
	38	132	–
	41	–	–
	44	–	–
	48	–	–
	51	–	–
	54	–	–

Copyright © 2014 by Sandvik Mining and Sandvik Construction. All rights reserved. This document or any portion thereof may not be reproduced in any manner whatsoever without the permission of Sandvik.

SANDVIK