
TECHNICAL SPECIFICATION

CONE CRUSHER CS SERIES
CS660





DIMENSIONS (mm)

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
5 100	1 600	860	1 240	1 400	2 810	970	2 895	5 346	1 497	2 156	1 528	2 103	993	1 766	951	1 252	691

WEIGHTS (kg)

Feed hopper	Spider cap	Topshell, complete	Mainshaft assembly complete	Eccentric, complete	Bottomshell assembly complete	Pinionshaft housing complete	Hydroset cylinder complete	Total Weight (approx.)	Oil tank
1 800	790	15 600	7 890	1 170	10 100	565	1 443	35 000	520

PERFORMANCE

Nominal capacities MTPH	Chamber	EC	C
	CSS	230–260	210–240
	GG	245	220
	SH	385	360
	ML	560	500
Max motor power (kW)		315	315
Ecc. Throw (mm)		20–40	20–40
CSS (mm)	35	–	335
	38	331–385	350–464
	41	345–514	364–542
	44	359–593	379–564
	48	378–624	399–593
	51	392–647	413–615
	54	406-670	428–637
	57	420–693	443–659
	60	433–716	458–681
	64	452–746	477–710
	70	480–792	507–589
	76	506–756	–
	83	540	–

Copyright © 2014 by Sandvik Mining and Sandvik Construction. All rights reserved. This document or any portion thereof may not be reproduced in any manner whatsoever without the permission of Sandvik.

SANDVIK